



DECLARATION OF PERFORMANCE
N° 0003-01-CPR-2014

1. Unique identification code of the product-type:
Baymer Spray 205 : Desmodur 44V20L
 Designation code. **PU EN 14315-1-CCC4-CT2(21)-GT5(21)-TFT8(21)-FRB40(21)-cs(10\y)200-MU110**

2. Intended use:
ThIB - Aislamiento térmico de edificios

3. Name and contact address of the manufacturer :
Baymer MaterialScience S.L.
Polígono Industrial s/n° 43110 LA CANONJA (Tarragona), ESPAÑA

4. System of assessment and verification of constancy of performance:
Sistema EVCP 3

5. Harmonized Standard: **EN 14315-1:2013**
 Notified bodies:
APPLUS / LGAI Technological Center, S.A. (370)
 (Performed task) Ensayos/Informes de reacción al fuego
 (System of assessment) EVCP 3
 (Test report) Informe 12/4579-1027 parte 2

CEIS / Centro de ensayos, innovación y servicios (1722)
 (Performed task) Ensayos/Informes de las otras características declaradas
 (System of assessment) EVCP 3
 (Test report) Informe CAT0010/14

6. Declared performance


<i>Essential characteristics</i>	<i>Performance</i>	<i>Harmonized technical specification</i>
Thermal resistance	See performance chart	EN 14315-1:2013
Reaction to fire	E	EN 13501-1
Close cell content	≥ 90%, CCC – 4	EN 14315-1:2013
Water vapour permeability (expressed as water vapour resistance factor μ)	110	UNE-EN12086:2013
Compressive strength	≥200 kPa	UNE-EN 826:2013
Durability of reaction to fire against ageing/degradation	Durability of reaction to fire against ageing/degradation	EN 14315-1:2013
Durability of thermal resistance against ageing/degradation	See performance chart	EN 14315-1:2013
Durability of compressive strength against ageing/degradation	Durability of compressive strength against ageing/degradation	EN 14315-1:2013

Performance chart:

Type of facing: None or diffusion open		
Thickness	Declared aged thermal conductivity (λ_D) W/m·K	Thermal resistance level (R_D) m ² ·K/W
30 mm	0,028	1,05
35 mm	0,028	1,25
40 mm	0,028	1,40
45 mm	0,028	1,60
50 mm	0,028	1,75
55 mm	0,028	1,95
60 mm	0,028	2,10
65 mm	0,028	2,30
70 mm	0,028	2,50
75 mm	0,028	2,65
80 mm	0,027	2,95
85 mm	0,027	3,15
90 mm	0,027	3,35
95 mm	0,027	3,55
100 mm	0,027	3,70
105 mm	0,027	3,90
110 mm	0,027	4,10
115 mm	0,027	4,25
120 mm	0,026	4,65
125 mm	0,026	4,85
130 mm	0,026	5,00
135 mm	0,026	5,20
140 mm	0,026	5,40
145 mm	0,026	5,60
150 mm	0,026	5,80
155 mm	0,026	6,00
160 mm	0,026	6,20
165 mm	0,026	6,40
170 mm	0,026	6,60
175 mm	0,026	6,75
180 mm	0,026	6,95
185 mm	0,026	7,15
190 mm	0,026	7,35
195 mm	0,026	7,55
200 mm	0,026	7,75

- The performance of the product identified above (see clause 1) is in conformity with the set of declared performances (see clause 6).
- This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above (see clause 3).
- Signed for and on behalf of the manufacturer by:

Signature



Dr. Benjamin Meseguer Vidagany
Head Research&Development
Bayer MaterialScience, S.L.
Polyurethane Systems Iberia

Place and date of emission

Tarragona (Spain), 01-10-2014

